

HOUSE PAINT

To obtain the best results the surface must be free of dirt and soot. If cracks or scales are present, the old paint must be burned or scraped off. The choice depends upon the condition of the surface.

Moisture often causes blistering, scaling and like trouble, therefore the surface must be absolutely dry before painting. It is best, not to paint, for at least two days after a rain. No painting should be done in frosty weather. Priming coats must be thinned with turpentine and brushed out thoroughly to a thin, even coat. Follow the directions on the label to insure a perfect job. Finishing coats must be applied within a reasonable length of time, allowing each coat to become thoroughly dry before another application is made. Our 100% pure house paint is the best that can be produced. The ingredients are Lead, Zinc, Linseed Oil and a small amount of Turpentine and Drier which will produce a beautiful and long lasting finish.

STAINS

Varnish Stain gives new life, new gloss and new color to old varnished surfaces. Our varnish stain is a tung oil, waterproof varnish incorporated with the necessary aniline dyes to make the six beautiful shades that are shown on the inside of this card. Clean the surface thoroughly before applying the stain.

Oil stain should be applied on bare wood, either new or old. Apply freely and wipe off surplus immediately after penetration, then apply finishing materials.

WALL FINISHES

The eight delicate shades are produced in three distinct types of wall finishes, being Gloss, Semi-Gloss, and Flat. These finishes are recommended for all interior surfaces such as plaster, wallboard, woodwork, metal and concrete. For new work use a priming coat of wall sealer. These finishes are made of high strength pigments with the combination of treated oils. This insures perfect hiding, ease of working, good flow and excellent durability. When the paints become dirty they will stand repeated washings without injuring the lustre or beauty.

QUICK DRY ENAMEL

The modern finish which is easy to apply on all surfaces. This enamel is produced with a processed tung oil that gives it extra smoothness and ease of brushing. One coat will cover without blemishes of any kind. We recommend this enamel on all surfaces inside or out, for it resists acid, alkali, heat, rust, cold and other destructive agencies. Four Hour Enamel dries to a hard, high gloss that can be washed repeatedly. The finish can be used in homes, offices, garages, factories, dairies, in fact all places where an excellent finish is required.

PORCH and FLOOR ENAMEL

An all-purpose floor enamel that is waterproof, weatherproof and highly resistant to general wear and tear. This floor enamel is made of a specially processed tung oil base. It is this scientifically treated oil that gives it the great wear resisting qualities, super-elasticity and superb smoothness. This all-purpose enamel can be used on any type of surface . . . wood or cement floors, furniture, boats, implements, garages, basements, and every other surface requiring utmost protection at no sacrifice to beauty. It can be used inside or outside with equally good results.



COLOR CHART OF MODERN FINISHES



MOLINE PAINT MFG. CO.

MOLINE, ILLINOIS

Foot of 16th St
under Arsenal
Bridge

HOUSE PAINT

OUR 100% PURE PAINT is as fine in quality as money and forty years of paint manufacturing experience knows how to produce.



VARNISH and OIL STAIN

VARNISH STAINS renew old varnish surfaces. Oil Stains used on soft wood produce exact duplicates of hard wood finishes.



VARNISH STAINS—10 SERIES
OIL STAINS—20 SERIES

WALL FINISHES

THESE COLORS ARE
FURNISHED IN
SEMI-GLOSS—700 SERIES
GLOSS—800 SERIES
FLAT—900 SERIES

THESE WALL FINISHES are the finest quality that can be produced. They brush easily, flow readily, dry hard and are very easily washed.



ON BARE PLASTER SURFACES
USE PIGMENT PRIMER FOR FIRST COAT

QUICK DRY ENAMEL

BRUSHES SMOOTHLY and is a quick drying enamel for use on furniture, woodwork, automobiles, boats, etc., washable.



PORCH and FLOOR ENAMEL

